

ARCHITECTURAL GRADE SERIES

# SPECIFICATION SHEET

1633 Staunton Ave Los Angeles, CA 90021

FAX. TEL.

(800) 727-9957 (800) 727-9262

E-Mail: sales@coronalighting.com

(213) 747-3234 (213) 747-4500

Down Lights Cast Brass

**Fixture Specifications:** 

Housing & Shroud: Corrosion Resistant Cast Brass.

PRODUCT #: CL-135B-BR

Finish: BR- Natural Brass. Natural toning process.

Lens: Clear and heat resistant convex glass.

Socket: Top grade fixed ceramic bi-pin socket, with lamp

retension clip to securely hold lamp in place.

12V, MR-16 halogen 50W max. L-BAB-C20 (20w) Lamp:

standard. LED lamps are also available. See lamp

guide, below for more information.

Wiring: Fixture is prewired with a 3-ft 18-2 direct burial cord.

> Wire connector available seperately, Universal connector CX-839 or gel filled wire nut CX-854 may be ordered

to Corona Lighting.

Gasket: Silicone double gasketed for water tight sealing

Knuckle: Adjustable cast brass knuckle with wing screw

Brass round Canopy with 1/2" NPT threaded Mounting:

female hub. CX-719B Brass mounting bracket

is also available.

**Electrical Notes:** A remote 12V transformer required, may be

ordered to Corona Lighting seperately. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are 9V-17V. Proper grease/lubricant is suggested on threaded parts during installation process.

Warranty: Limited lifetime warranty on fixture housing against

manufacturer's defects.





### 3.5W and 5W

#### **ACCESSORY** AVAILABLE LED LAMPS (Corona LED lamps have a five (5) year limited warranty against manufacturer's defects)



### **Mounting Bracket** CX-719B-BR

**BR-** Natural Brass

Fixtures also available with CX-719B-BR. Price remains the same as listed

LAMP NUMBER	WATTS		LUMEN	TEMP.
L-ED16-COB5W-SP	5	15° Spot	450	2700K
L-ED16-COB5W-FL	5	38° Flood	450	2700K
L-ED16-COB5W-WF	5	60° Wide Flood	450	2700K
L-ED16-COB5W-SP3K	5	15° Spot	470	3000K
L-ED16-COB5W-FL3K	-	38° Flood	470	3000K
L-ED16-COB5W-WF3k	5	60° Wide Flood	470	3000K
. =5.40.014.05				
L-ED16-3W-SP	3.5	15° Spot	270	2700K
L-ED16-3W-FL	3.5	45° Flood	270	2700K
L-ED16-3W-WF	3.5	60° Wide Flood	270	2700K
L-ED16-5W-SP	5	15° Spot	350	2700K
L-ED16-5W-FL	5	45° Flood	350	2700K
L-ED16-5W-WF	5	60° Wide Flood	350	2700K
For more additional Lamps, and accessories visit Coronalighting.com				

## JOB INFORMATION

TYPE: DATE:

**JOB NAME & ADDRESS:** 

PRODUCT #:

**TOTAL QUANTITY:** 

LAMP TYPE & WATTAGE:

TRANSFORMER:

CONTRACTOR:

SPECIFIER:

• When ordering LED lamp with a fixture your part number should follow the format below:

• CL - product # - lamp - wattage - lamp angle CL - 135B-AB - L-ED16 - 5W -

Example: CL-135B-BR-L-ED16-5W-FL

Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.