

TEL.

FAX.



(800) 727-9957

(800) 727-9262

(213) 747-3234



Faceplate:

SPECIFICATION SHEET

E-Mail: sales@coronalighting.com

0

PRODUCT #: CL-308-BR

Cast Brass

Fixture Specifications:

Housing: Corrosion resistant cast brass.

Cast brass with 316 marine grade stainless

steel screws.

Finish: BR- Natural Brass. Natural toning process.

Also available in AB- Antique Bronze

Lens: Clear, tempered, and heat resistant glass.

Socket: Top grade loose ceramic bi-pin socket, spring

loaded design.

Lamp: 12V, MR-16, 50W max.

Available in LED (3.5W & 5W) or without lamp.

See the Lamp Guide below for more information.

Gasket: Silicone "O" ring seals faceplate to housing

providing water tight protection.

Underwater

Applications:

To be used in fountains, ponds, and waterfalls. Do not use in swimming pools, lakes or spas.

Wiring: Fixture is prewired with a 30-ft 18-2 SJT-W water

resistant cord. Longer cord lengths also available.

Mounting: Fully adjustable arms with solid brass thumb screws

> to provide light aiming. Fixture is mounted on a heavy duty brass bracket for a firm and stable underwater

placement.

Electrical Notes: A remote 12V transformer is required. Options are

available from Corona Lighting.

53/4"

Voltage range for LED lamps are 9V-17V.

Warranty: Limited lifetime warranty on fixture against

manufacturer's defects.





3.5W and 5W	
AVAILABLE LED LAMPS (Corona LED lamps have a five (5) year limited warranty against manufacturer's defects)	JOB I

		BEAM		COLOR &	RATED	HALOGEN
LAMP NUMBER	WATTS	SPREAD	LUMEN	TEMP.	HOURS	EQUIVALENT
L-ED16-3W-SP	3.5	15° Spot	270	2700K	50,000	25 Watt
L-ED16-3W-FL	3.5	45° Flood	270	2700K	50,000	25 Watt
L-ED16-3W-WF	3.5	60° Wide Flood	270	2700K	50,000	25 Watt
L-ED16-5W-SP	5	15° Spot	350	2700K	50,000	40 Watt
L-ED16-5W-FL	5	45° Flood	350	2700K	50,000	40 Watt
L-ED16-5W-WF	5	60° Wide Flood	350	2700K	50,000	40 Watt
L-ED16-COB5W-SP	5	15° Spot	450	2700K	50,000	50 Watt
L-ED16-COB5W-FL	5	38° Flood	450	2700K	50,000	50 Watt
L-ED16-COB5W-WF	5	60° Wide Flood	450	2700K	50,000	50 Watt
L-ED16-COB5W-SP3K	5	15° Spot	470	3000K	50,000	50 Watt
L-ED16-COB5W-FL3K	5	38° Flood	470	3000K	50,000	50 Watt
L-ED16-COB5W-WF3K	5	60° Wide Flood	470	3000K	50,000	50 Watt
					•	

■ Single color MR-16 LED available in AMBER, BLUE, GREEN, PURPLE, RED and VIOLET

• When ordering LED lamp with a fixture your part number should follow the format below: • CL - product # - lamp - wattage - lamp angle

Example: CL-308-BR-L-ED16-5W-FL CL - 308-BR - L-ED16 -5W FL

Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.

INFORMATION

TYPE: DATE:

JOB NAME & ADDRESS:

PRODUCT #:

TOTAL QUANTITY:

LAMP TYPE & WATTAGE:

TRANSFORMER:

CONTRACTOR:

SPECIFIER:



ACCESSORIES SHEET

1633 Staunton Ave Los Angeles, CA 90021

TEL. FAX. (800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

E-Mail: sales@coronalighting.com

PRODUCT # : CL-308-BR

• Underwater • Cast Brass

Special Lenses & Honeycomb Louvers

CX-238 MR-16 Snap-on holder, **Silver Plated**CX-239 MR-16 honeycomb louver, **Black**

CX-240-AM MR-16 color lens, Amber
CX-240-BL MR-16 color lens, Blue
CX-240-GR MR-16 color lens, Green
CX-240-RD MR-16 color lens, Red
CX-240-YL MR-16 color lens, Yellow
CX-241 MR-16 lens, Linear Spread

CX-242 MR-16 lens, **Frosted**CX-243 MR-16 lens, **Prismatic**

For MR-16 Lenses and Louvers, you will need the CX-238

