

ARCHITECTURAL GRADE SERIES

SPECIFICATION SHEET

1633 Staunton Ave Los Angeles, CA 90021

FAX. TEL.

(800) 727-9957 (800) 727-9262 (213) 747-3234 (213) 747-4500

E-Mail: sales@coronalighting.com

PRODUCT #: CL-313-BR

• Underwater Light

Brass

Fixture Specifications:

Housing: Solid Brass

Finish:

Lens:

Socket:

BR- Natural Brass

Clear, tempered, and heat resistant glass.

Lens is fully sealed for underwater usage.

PAR36 Screw Terminal

12V, PAR36 50W Max. Lamp:

Available in LED (6W, 10W or 13W) or without lamp.

See Lamp Guide below for more information.

Gasket: Silicone "O" ring seals faceplate to housing

providing water tight protection.

Wiring: Fixture is prewired with a 30ft 18-2 SJT-W water

resistant cord. Other cord lengths are also available.

Mounting: Fully adjustable mounting arms to provide light

> aiming. Fixture is mounted on a heavy duty round base for firm and stable underwater placement.

Electrical Notes: A remote 12V transformer is required. Options are

available from Corona Lighting. Voltage range for

LED lamps are 9V-24V.

Applications: To be installed in waterfalls, shallow ponds and

Fountains.


Do not use in swimming pools, lakes or spas.

Warranty: Limited lifetime warranty on faceplate against

manufacturer's defects.







AVAILABLE LED LAMPS (Corona LED lamps have a five (5) year limited warranty against manufacturer's defects)

		BEAM		_ COLOR &	RATED	HALOGEN EQUIVALENT
LAMP NUMBER	WATTS	SPREAD	LUMEN	TEMP.	HOURS	
L-ED36-6W-FL	6	45° Flood	610	2700K	50,000	35 Watt
L-ED36-6W-WF	6	60° Wide Flood	610	2700K	50,000	35 Watt
L-ED36-10W-FL	10	45° Flood	800	2700K	50,000	50 Watt
L-ED36-10W-WF	10	60° Wide Flood	800	2700K	50,000	50 Watt
L-ED36-13W-FL	13	45° Flood	1150	2700K	50,000	75 Watt
L-ED36-13W-WF	13	60° Wide Flood	1150	2700K	50,000	75 Watt

For more additional Lamps, and accessories visit Coronalighting.com

JOB INFORMATION

TYPE: DATE:

JOB NAME & ADDRESS:

PRODUCT #:

TOTAL QUANTITY:

LAMP TYPE & WATTAGE:

TRANSFORMER:

CONTRACTOR:

SPECIFIER:

wattage - lamp angle Example: CL-313-BR-L-ED36-9W-FL CL - 313-BR - L-ED36 -9W

Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.

[•] If you are ordering LED lamps you should follow the format below: