CL-333-SS			
Product Specification Sheet			
HOUSING:	Solid stainless steel fixture, suspended inside a reversible flat or angled cut PVC sleeve, provides in-ground support. Fixture is adjustable inside the PVC sleeve for light aiming.		
FINISH:	SS -Natural Stainless Steel fixture. PVC sleeve available in black only.		
LENS:	Clear, tempered and heat resistant glass with a silicone gasket. See accessories & parts for special effect lenses,	CL-333-SS	
	honeycomb louver and frosted glass lens CX-380-FR.		CX-854 DIRECT BURIAL WIRENUT AVAILABLE
LAMP TYPE:	12V, MR-16 halogen, 35W max. See lamp guide for LED and color MR-16 lamps.	$\begin{array}{c} \begin{array}{c} \begin{array}{c} \begin{array}{c} -37/8" \rightarrow \\ 1+21/2" \rightarrow \end{array} \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \begin{array}{c} \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \begin{array}{c} \end{array} \\ \begin{array}{c} \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} $	
MOUNTING:	In-ground direct burial or concrete encasement. Use gravel for proper drainage. Angle cut end required to be installed 3" above the ground.		CORONA
WIRING:	Fixture is prewired with a 3-foot pigtail of direct burial cable.	8" ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓	Lighting WWW.CORONALIGHTING.COM Tel: 800-727-9262 213-747-4500 Fax: 800-727-9957 213-747-3234

- Fixture is supplied with 20W MR-16 lamp.Remote 12 Volt transformer is required.
- See transformers and accessories for variety of options and choices.