

**SPECIFICATION SHEET** 

(800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

TEL.

FAX.

1

1633 Staunton Ave Los Angeles, CA 90021

E-Mail: sales@coronalighting.com

A securities of the power of th	ted steel mour ket ailable in <b>AB</b> - due to artistic luminum: <b>BK</b> - Vhite <b>M</b> -Gun Metal, <b>SI</b> - Silver polycarbonate ad sealed to fa S.C. Bayonet s c, 18W max. 2W & 2.5W) o de below for n	Antique Broi process. -Black, <b>BZ</b> -Br , <b>OC</b> -old Cop e lens aceplate. socket. or without lam more information	ronze, oper, np. tion.	Wiring: Mounti Electric	ng: cal Notes: ty:	Fixture comes prewired with a 12 inch direct burialcord. Wire connector sold seperately. Silicone filled wire nut ( <b>CX-854</b> ) are available from Corona Lighting. Recessed box to mount into concrete, brick or masonry. Outdoor use only. A remote 12V transformer is required. Options are available from Corona Lighting. Voltage range for LED lamps are 8V-21V. <b>AB, GM, OC, SI</b> , and <b>RC</b> - Limited lifetime warrant on fixture housing and faceplate against manufacturer's defects. <b>BK, BZ, RT</b> and <b>WH</b> - Five year warranty on fixtur housing and faceplate against manufacturer's defects.
A.C. Bayonet Sock tramped brass av. B finish will vary d lso available in a T- Rust <b>or WH</b> -W tramped Metal: <b>G</b> <b>C</b> - Raw Copper, ligh impact white ens is secured ar top grade, fixed S 2V, S.C. Bayonet vailable in LED (2 ee the Lamp Guid ilicone gasket pro	ket ailable in <b>AB</b> - due to artistic luminum: <b>BK</b> - Vhite <b>M</b> -Gun Metal, <b>SI</b> - Silver polycarbonate nd sealed to fa S.C. Bayonet s a, 18W max. 2W & 2.5W) o de below for n	Antique Broi process. -Black, <b>BZ</b> -Br , <b>OC</b> -old Cop e lens aceplate. socket. or without lam more information	ronze, oper, np. tion.	Mounti Electric	ng: cal Notes: ty:	burialcord. Wire connector sold seperately. Silicone filled wire nut ( <b>CX-854</b> ) are available from Corona Lighting. Recessed box to mount into concrete, brick or masonry. Outdoor use only. A remote 12V transformer is required. Options are available from Corona Lighting. Voltage range for LED lamps are 8V-21V. <b>AB</b> , <b>GM</b> , <b>OC</b> , <b>SI</b> , and <b>RC</b> - Limited lifetime warrant on fixture housing and faceplate against manufacturer's defects. <b>BK</b> , <b>BZ</b> , <b>RT</b> and <b>WH</b> - Five year warranty on fixture housing and faceplate against manufacturer's defects.
Iso available in a RT- Rust or WH-W tramped Metal: G C- Raw Copper, ligh impact white ens is secured an op grade, fixed S 2V, S.C. Bayonet vailable in LED (2 ee the Lamp Guidilicone gasket pro	luminum: <b>BK</b> - Vhite <b>M</b> -Gun Metal, <b>SI</b> - Silver polycarbonate ad sealed to fa S.C. Bayonet s c, 18W max. 2W & 2.5W) o de below for n	Black, <b>BZ</b> -Br , <b>OC</b> -old Cop e lens aceplate. socket. or without lam more information	pper, np. tion.	Electric	cal Notes:	Recessed box to mount into concrete, brick or masonry. Outdoor use only. A remote 12V transformer is required. Options are available from Corona Lighting. Voltage range for LED lamps are 8V-21V. AB, GM, OC, SI, and RC- Limited lifetime warrant on fixture housing and faceplate against manufacturer's defects. BK, BZ, RT and WH- Five year warranty on fixture housing and faceplate against manufacturer's defects.
<b>RC</b> - Raw Copper, ligh impact white ens is secured ar op grade, fixed S 2V, S.C. Bayonet vailable in LED (2 ee the Lamp Guid ilicone gasket pro	SI- Silver polycarbonate nd sealed to fa S.C. Bayonet s a, 18W max. 2W & 2.5W) o de below for n	e lens aceplate. socket. or without lam more informa	ıp.		ity:	available from Corona Lighting. Voltage range for LED lamps are 8V-21V. AB, GM, OC, SI, and RC- Limited lifetime warrant on fixture housing and faceplate against manufacturer's defects. BK, BZ, RT and WH- Five year warranty on fixture housing and faceplate against manufacturer's defects.
ens is secured ar op grade, fixed S 2V, S.C. Bayonet vailable in LED (2 ee the Lamp Guid ilicone gasket pro	nd sealed to fa S.C. Bayonet s , 18W max. 2W & 2.5W) o de below for n	aceplate. socket. or without lam more informat	tion.	Warran		AB, GM, OC, SI, and RC- Limited lifetime warrant on fixture housing and faceplate against manufacturer's defects. BK, BZ, RT and WH- Five year warranty on fixture housing and faceplate against manufacturer's defects.
2V, S.C. Bayonet vailable in LED (2 ee the Lamp Guid ilicone gasket pro	:, 18W max. 2W & 2.5W) o de below for n	or without lam more informa	tion.	Warran		on fixture housing and faceplate against manufacturer's defects. BK, BZ, RT and WH- Five year warranty on fixtur housing and faceplate against manufacturer's defects.
vailable in LED (2 ee the Lamp Guid ilicone gasket pro	2W & 2.5W) o de below for n	more information	tion.			BK, BZ, RT and WH- Five year warranty on fixtur housing and faceplate against manufacturer's defects.
	oviding water-	tight protection	on.			
(3						
			2W			4 <sup>3</sup> / <sub>8</sub> "
ED LAMPS (Cord						
WATTS	SPREAD	LUMEN	TEMP.	HOURS	EQUIVALEN	
2 2.5	360° 180°	200 240	2700K 2700K	25,000 25,000	20 Watt 35 Watt	JOB NAME & ADDRESS:
2 ( 2.5	360° 180°	210 250	3000K 3000K	25,000 25,000	20 Watt 35 Watt	
2	360°	170	2000K	25,000	20 Watt	PRODUCT #:
amps, and accessories	visit Coronalightin	ng.com				TOTAL QUANTITY: LAMP TYPE & WATTAGE: TRANSFORMER: CONTRACTOR: SPECIFIER:
<	WATTS           2           2.5           2           2.5           2           2.5           2           2.5	WATTS         SPREAD           2         360°           2.5         180°           2         360°           2.5         180°           2         360°           2.5         180°           2         360°           2.5         360°	BEAM           WATTS         SPREAD         LUMEN           2         360°         200           2.5         180°         240           2         360°         210           2.5         180°         250	BEAM         Colore LED lamps have a five (5) year limited warra           BEAM         COLOR & TEMP.           2         360°         200         2700K           2.5         180°         240         2700K           2         360°         210         3000K           2.5         180°         250         3000K           2.5         180°         250         3000K           2.5         180°         170         2000K	BEAM         Colorest Colores Colorest Colores Colorest Colorest Colorest Color	WATTS         SPREAD         LUMEN         TEMP.         HOURS         EQUIVALED           2         360°         200         2700K         25,000         20 Watt           2.5         180°         240         2700K         25,000         35 Watt           2         360°         210         3000K         25,000         20 Watt           2.5         180°         250         3000K         25,000         35 Watt           2         360°         170         2000K         25,000         20 Watt



• Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.



## **ACCESSORIES SHEET**

 1633 Staunton Ave

 Los Angeles, CA 90021

 TEL.
 FAX.

 (800) 727-9262
 (800) 727-9957

 (213) 747-4500
 (213) 747-3234

E-Mail: sales@coronalighting.com

## PRODUCT #: CL-361B-AB

Step Light

CX-731


**Mount Box** 

Steel & Brass

## Faceplates

CX-873B-AB Brass, 3 louver faceplate with white acrylic lens.

Stamped brass available in **AB**- Antique Bronze. AB finish will vary due to artistic process. Also available in aluminum: **BK**-Black, **BZ**-Bronze, **RT**- Rust **or WH**-White Stamped Metal: **GM**-Gun Metal, **OC**-old Copper, **RC**- Raw Copper, **SI**- Silver



2<sup>1</sup>/<sub>8</sub>"

Steel Mount Box, No Lamp

Lamp not included. Shown for demonstration.

## **Cable Connector**

CX-854 Direct Burial Silicone Filled Wire Nut, Tan

