

SPECIFICATION SHEET

 1633 Staunton Ave

 Los Angeles, CA
 90021

 TEL.
 FAX.

 (800) 727-9262
 (800) 727-9957

 (213) 747-4500
 (213) 747-3234

VALUE GRA	ADE SERIES		3	PE	JFIC/		N 2H	E-Mail: sal	les@coronalighting.com
PRODUCT # : CL-512			•Direc	•Directional Lights		• Aluminum			
Fixture	e Specif	icatio	ons:						
Housing:	Die-cast alu	minum.				Gaske		Silicone "O" ring seals face p	late to housing providing
Finish:	Polyester U	V powde	er coated, availab	le in BK	Black			weather-tight protection.	
Lens:	Clear, tempe gasket.	ered and	l heat resistant g	lass with	silicone	Knuck		Cast aluminum adjustable kr shaped screw. ½" NPT threa	aded male hub on bottom.
Socket:	Top grade c	eramic b	i-pin socket, with	n retentio	n clip.	Mount	ing Spike:	8" Black ABS spike with ½" N hub.	IPT threaded female
Lamp:	12V, MR-16, 50W max. Available in LED (3.5W & 5W) or without lamp. See the Lamp Guide below for more information.			Electri	cal Notes:	A remote 12V transformer is required. Options are available from Corona Lighting. Voltage range for LED lamps are 9V-17V. Proper grease/lubricant is suggested on			
Wiring:	Fixture is prewired with a 3ft 18-2 SPT1-W direct burial cord. Wire connector sold seperately. Universal							threaded parts during installation process.	
	connector (CX-839) and silicone filled wire nut (CX-854) are available from Corona Lighting.			Warra	nty:	One (1) year warranty on fixt manufacturer's defects	ure and housing against		
AVAILAB		MPS (Co	rona LED lamps have	a five (5) γ		ED V and 5	W ,	s) JOB INFORMATION	
LAMP N	UMBER	WATTS	BEAM SPREAD	LUMEN	COLOR & TEMP.	RATED HOURS	HALOGEN EQUIVALEN	TYPE:	DATE:
L-ED16-3W		3.5	15° Spot	270	2700K	50,000	25 Watt		_ .
L-ED16-3W		3.5	45° Flood	270	2700K	50,000	25 Watt	JOB NAME & ADDRESS:	
L-ED16-3W		3.5	60° Wide Flood	270	2700K	50,000	25 Watt		
L-ED16-5W L-ED16-5W		5 5	15° Spot 45° Flood	350 350	2700K 2700K	50,000 50,000	40 Watt 40 Watt	PRODUCT #:	
L-ED16-5W		5 5	45° Flood 60° Wide Flood	350 350	2700K 2700K	50,000 50,000	40 Watt 40 Watt	TOTAL QUANTITY:	
L-ED16-CC	B5W-SP	5	15° Spot	450	2700K	50,000	50 Watt	LAMP TYPE & WATTAGE:	
L-ED16-CO		5	38° Flood	450	2700K	50,000	50 Watt	TRANSFORMED	
L-ED16-CC		5	60° Wide Flood	450	2700K	50,000	50 Watt	TRANSFORMER:	
)B5W-SP3K)B5W-FL3K	5 5	15° Spot 38° Flood	470 470	3000K 3000K	50,000 50,000	50 Watt 50 Watt	CONTRACTOR:	
	B5W-WF3K	5 5	60° Wide Flood	470 470	3000K	50,000 50,000	50 Watt	SPECIFIER:	
Single color M	R-16 LED availab	ole in AMB	ER, BLUE, GREEN, F	PURPLE, RI	ED and VIOLET			7	
-			ure your part numb			at below:			
	1 4 11								

•CL - product # - lamp - wattage - lamp angle

CL - 512-BK - L-ED16 - 5W - FL Example: CL-512-BK-L-ED16-5W-FL

• Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.




ACCESSORIES SHEET

PRODUCT # : CL-512

Mounting Pedestals

CX-601-BK	1" PVC Mounting Pedestal, 1/2" NPT, Black
CX-601-VG	1" PVC Mounting Pedestal, 1/2" NPT, Verde Green
CX-603-BK	3" PVC Mounting Pedestal, ½" NPT Female Brass Hub on top, Black
CX-603-VG	3" PVC Mounting Pedestal, ¹ / ₂ " NPT Female Brass Hub on top, Verde Green
	40"



CX-603-BK

1" PVC Adjustable Mounting Pedestal, ½" NPT, Black
1" PVC Cap, ½" NPT, Black
1" PVC Cap, ½" NPT, Verde Green
2" PVC Cap, ½" NPT, Black
2" PVC Cap, 1⁄2" NPT, Verde Green
3" PVC Cap, ½" NPT Female Brass Hub, Black
3" PVC Cap, $1\!\!\!/_2$ " NPT Female Brass Hub, Verde Green

Los Angeles, CA 90021 TEL. FAX. (800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

E-Mail: sales@coronalighting.com

1633 Staunton Ave

```
    Directional Lights
```

Aluminum

Mounting Canopies

•	•
CX-701-BK	Aluminum Round Canopy , ½ NPT, Black
CX-702-BK	Aluminum Rectangular Canopy, ½ NPT, Black
CX-703	Aluminum tree mount canopy ½ NPT Finishes: BK - Black, BZ - Bronze, GR - Green, GT - Granite, RT - Rust, VG - Verde Green, WH - White
CX-720	Aluminum Tree mount Canopy with 9" Rubber Strap stretches to 14" Finishes: BK - Black, BZ - Bronze, GR - Green, GT - Granite, RT - Rust, VG - Verde Green, WH - White
CX-721	Aluminum Tree mount Canopy with 15" Rubber Strap stretches to 22" Finishes: BK- Black, BZ- Bronze, GR- Green, GT- Granite, RT- Rust, VG- Verde Green, WH- White
CX-722	Aluminum Tree mount Canopy with 22" Rubber Strap stretches to 33" Finishes: BK - Black, BZ - Bronze, GR - Green, GT - Granite, RT - Rust, VG - Verde Green, WH - White
CX-723	Aluminum Tree mount Canopy with 31" Rubber Strap stretches to 45" Finishes: BK - Black, BZ - Bronze, GR - Green, GT - Granite, RT - Rust, VG - Verde Green, WH - White

Mounting Risers

CX-671	6" Aluminum Riser, ½ NPT Male/Female Finishes: BK - Black, BZ - Bronze, GR - Green, GT - Granite, RT - Rust, VG - Verde Green, WH - White
CX-672	12" Aluminum Riser, ½ NPT Male/Female Finishes: BK- Black, BZ- Bronze, GR- Green, GT- Granite, RT- Rust, VG- Verde Green, WH- White
CX-673	18" Aluminum Riser, ½ NPT Male/Female Finishes: BK- Black, BZ- Bronze, GR- Green, GT- Granite, RT- Rust, VG- Verde Green, WH- White
	СХ-671-ВК 6″

CX-671-BK 6

CX-672-BK 12"

CX-673-BK 18"

	СХ-647-ВК
CX-646-BK	8" ABS Spike, ½" NPT, Black
CX-646-BR	8" ABS Spike, ½" NPT, Natural Brass
CX-646-SS	8" ABS Spike, 1/2" NPT, Stainless Steel
CX-647-BK	10.5" Heavy Duty ABS Spike, ½" NPT, Black

—— 4½"— СХ-703-ВК

8.5" ABS Spike, 1/2" NPT, Black

8.5" ABS Spike, 1/2" NPT, Bronze

8.5" ABS Spike, 1/2" NPT, Bronze

101/2"

Ground Spikes

CX-642-BK

CX-642-BZ

CX-643-BZ

СХ-722-ВК

3"




ACCESSORIES SHEET

Directional Lights

1633 Staunton Ave Los Angeles, CA 90021 TEL. FAX. (800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

E-Mail: sales@coronalighting.com

Aluminum



Mounting Brackets



Special Lenses & Honeycomb Louvers CX-238 MR-16 Snap-on holder, Silver Plated CX-239 MR-16 honeycomb louver, Black CX-240-AM MR-16 color lens, Amber CX-240-BL MR-16 color lens, Blue CX-240-GR MR-16 color lens, Green CX-240-RD MR-16 color lens, Red CX-240-YL MR-16 color lens, Yellow CX-241 MR-16 lens, Linear Spread CX-242 MR-16 lens, Frosted CX-243 MR-16 lens, Prismatic

• For MR-16 Lenses and Louvers, you will need the CX-238



