

SPECIFICATION SHEET

1633 Staunton Ave Los Angeles, CA 90021 TEL. FAX. (800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

E-Mail: sales@coronalighting.com

1


FILOL	OUCT # : C							
Fixture	Specificatio	ons:						
Housing &	lousing & Shroud: Corrosion resistant Cast Brass.					kle:	Adjustable cast brass knuckle with thumb screw	
Stem:	tem: Solid brass pipe with ½" NPT on bottom.			Wirin	Wiring:	Fixture is prewired with a 3ft, 18-2 direct burial cord. Wire connector available seperately. Universal connector (CX-839) and silicone filled wire nut (CX-854) are available from Corona Lighting.		
Finish:	GM- Gun Metal . Natural toning process. GM finish will vary due to artistic process. Also available in AB- Antique Bronze			-				
Lens:	Frosted and heat resistant tempered flat glass. Supplied with extra clear glass lens, linear glass lens, and honeycomb louver.			Moun	ting Spike:	Standard injection molded spike with ½" NPT threaded female hub.		
Socket:	Top grade fixed ce	eramic bi-pin s	ocket.		Elect	Electrical Notes:	A remote 12V transformer is required. Options are	
Lamp:	12V T3, 35W max. Available in LED (2W & 2.5W) or without lamp. See the Lamp Guide below for more information.					available from Corona Lighting. Voltage range for LED lamps are 8V-21V. Some assembly needed. Proper grease/lubricant suggested on threaded parts during installation.		
Gasket: Silicone gasket for water tight sealing.			ealing.	Warranty:		anty:	Limited lifetime warranty on fixture housing and stem against manufacturer's defects.	
							option	
	CL-733B-GM 18" Standard stem shown		18"	L 2W a	E D and 2.5		CL-733B-GM-12 12" stem available	
AVAILABL	18" Standard	rona LED lamps ha					CL-733B-GM-12 12" stem available	
	18" Standard stem shown E LED LAMPS (Col	rona LED lamps ha BE/ SPREAD	ave a five (5) ye				CL-733B-GM-12 12" stem available	
AMP NUMBE -EDT3-2W	18" Standard stem shown E LED LAMPS (Co. ER WATTS 2	BE/ SPREAD 360°	ave a five (5) ye AM LUMEN 200	ear limited warrar _ COLOR & TEMP. 2700K	nty against man RATED HOURS 25,000	ufacturer's defects HALOGEN EQUIVALENT 20 Watt	CL-733B-GM-12 12" stem available JOB INFORMATION TYPE: DATE:	
. AMP NUMBE EDT3-2W EDT3-2.5V EDT3-2W-	18" Standard stem shown E LED LAMPS (Col ER WATTS 2 V 2.5 3K 2	BE/ SPREAD 360° 180° 360°	ave a five (5) ye AM LUMEN	ar limited warrar COLOR & TEMP. 2700K 2700K 3000K	nty against man RATED HOURS 25,000 25,000 25,000	ufacturer's defects HALOGEN EQUIVALENT 20 Watt 35 Watt 20 Watt	CL-733B-GM-12 12" stem available	
AMP NUMBE -EDT3-2W -EDT3-2.5V -EDT3-2W- -EDT3-2.5V	18" Standard stem shown E LED LAMPS (Col ER WATTS 2 2.5 3K 2 V-3K 2.5	BE/ SPREAD 360° 180°	Ave a five (5) yee Ave a five (5) yee AM LUMEN 200 240 210 250	ar limited warrar COLOR & TEMP. 2700K 2700K 3000K 3000K	nty against man RATED HOURS 25,000 25,000	ufacturer's defects HALOGEN EQUIVALENT 20 Watt 35 Watt	CL-733B-GM-12 12" stem available JOB INFORMATION TYPE: DATE:	
AMP NUMBE -EDT3-2W -EDT3-2.5V -EDT3-2W- -EDT3-2.5V -EDT3-AM*	18" Standard stem shown E LED LAMPS (Control ER WATTS 2 2.5 3K 2 V-3K 2.5 2 2.5	BE/ SPREAD 360° 180° 360° 180°	Ave a five (5) yee Ave a five (5) yee AM LUMEN 200 240 210	ar limited warrar COLOR & TEMP. 2700K 2700K 3000K	nty against man RATED HOURS 25,000 25,000 25,000 25,000	ufacturer's defects HALOGEN EQUIVALENT 20 Watt 35 Watt 20 Watt 35 Watt	CL-733B-GM-12 12" stem available JOB INFORMATION TYPE: DATE: JOB NAME & ADDRESS:	
AMP NUMBE -EDT3-2W -EDT3-2.5V -EDT3-2W- -EDT3-2.5V -EDT3-AM*	18" Standard stem shown E LED LAMPS (Control ER WATTS 2 2.5 3K 2 V-3K 2.5 2 2.5	BE/ SPREAD 360° 180° 360° 180° 360° 360°	ave a five (5) ye AM LUMEN 200 240 210 250 170	ar limited warrar COLOR & TEMP. 2700K 2700K 3000K 3000K	nty against man RATED HOURS 25,000 25,000 25,000 25,000	ufacturer's defects HALOGEN EQUIVALENT 20 Watt 35 Watt 20 Watt 35 Watt	CL-733B-GM-12 12" stem available JOB INFORMATION TYPE: DATE: JOB NAME & ADDRESS: PRODUCT #:	
AMP NUMBE -EDT3-2W -EDT3-2.5V -EDT3-2W- -EDT3-2.5V -EDT3-AM*	18" Standard stem shown E LED LAMPS (Context E LED LAMPS (Context V 2 V 2.5 3K 2 V-3K 2.5 2 2 2 2 2 2 2 2 2 3K 2 2 2	BE/ SPREAD 360° 180° 360° 180° 360° 360°	ave a five (5) ye AM LUMEN 200 240 210 250 170	ar limited warrar COLOR & TEMP. 2700K 2700K 3000K 3000K	nty against man RATED HOURS 25,000 25,000 25,000 25,000	ufacturer's defects HALOGEN EQUIVALENT 20 Watt 35 Watt 20 Watt 35 Watt	CL-733B-GM-12 12" stem available JOB INFORMATION TYPE: DATE: JOB NAME & ADDRESS: PRODUCT #: TOTAL QUANTITY:	
AMP NUMBE -EDT3-2W -EDT3-2.5V -EDT3-2W- -EDT3-2.5V -EDT3-AM*	18" Standard stem shown E LED LAMPS (Context E LED LAMPS (Context V 2 V 2.5 3K 2 V-3K 2.5 2 2 2 2 2 2 2 2 2 3K 2 2 2	BE/ SPREAD 360° 180° 360° 180° 360° 360°	ave a five (5) ye AM LUMEN 200 240 210 250 170	ar limited warrar COLOR & TEMP. 2700K 2700K 3000K 3000K	nty against man RATED HOURS 25,000 25,000 25,000 25,000	ufacturer's defects HALOGEN EQUIVALENT 20 Watt 35 Watt 20 Watt 35 Watt	CL-733B-GM-12 12" stem available JOB INFORMATION TYPE: DATE: JOB NAME & ADDRESS: PRODUCT #: TOTAL QUANTITY: LAMP TYPE & WATTAGE: TRANSFORMER:	
AMP NUMBE -EDT3-2W -EDT3-2.5V -EDT3-2W- -EDT3-2.5V -EDT3-AM*	18" Standard stem shown E LED LAMPS (Context E LED LAMPS (Context V 2 V 2.5 3K 2 V-3K 2.5 2 2 2 2 2 2 2 2 2 3K 2 2 2	BE/ SPREAD 360° 180° 360° 180° 360° 360°	ave a five (5) ye AM LUMEN 200 240 210 250 170	ar limited warrar COLOR & TEMP. 2700K 2700K 3000K 3000K	nty against man RATED HOURS 25,000 25,000 25,000 25,000	ufacturer's defects HALOGEN EQUIVALENT 20 Watt 35 Watt 20 Watt 35 Watt	CL-733B-GM-12 12" stem available JOB INFORMATION TYPE: DATE: JOB NAME & ADDRESS: PRODUCT #: TOTAL QUANTITY: LAMP TYPE & WATTAGE:	
AMP NUMBE -EDT3-2W -EDT3-2.5V -EDT3-2W- -EDT3-2.5V -EDT3-AM*	18" Standard stem shown E LED LAMPS (Context E LED LAMPS (Context V 2 V 2.5 3K 2 V-3K 2.5 2 2 2 2 2 2 2 2 2 3K 2 2 2	BE/ SPREAD 360° 180° 360° 180° 360° 360°	ave a five (5) ye AM LUMEN 200 240 210 250 170	ar limited warrar COLOR & TEMP. 2700K 2700K 3000K 3000K	nty against man RATED HOURS 25,000 25,000 25,000 25,000	ufacturer's defects HALOGEN EQUIVALENT 20 Watt 35 Watt 20 Watt 35 Watt	CL-733B-GM-12 12" stem available JOB INFORMATION TYPE: DATE: JOB NAME & ADDRESS: PRODUCT #: TOTAL QUANTITY: LAMP TYPE & WATTAGE: TRANSFORMER: CONTRACTOR:	

CL - 733B-GM - 12 - L-EDT3 - 2W-3K

• Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.

Example: CL-733B-GM-12-L-EDT3-2W-3K





on top, Verde Green

CX-603-BK

CX-604-BK	1" PVC Adjustable Mounting Pedestal, ½" NPT, Black
CX-621-BK	1" PVC Cap, ½" NPT, Black
CX-621-VG	1" PVC Cap, 1/2" NPT, Verde Green
CX-622-BK	2" PVC Cap, ½" NPT, Black
CX-622-VG	2" PVC Cap, 1/2" NPT, Verde Green
CX-624-BK	3" PVC Cap, ½" NPT Female Brass Hub, Black
CX-624-VG	3" PVC Cap, ½" NPT Female Brass Hub, Verde Green

Ground Spikes CX-642-BK 8.5" ABS Spike, ½" NPT, Black CX-642-BZ 8.5" ABS Spike, ½" NPT, Bronze CX-643-BZ 8.5" ABS Spike, ½" NPT, Bronze 10½" 10½" CX-646-BK 8" ABS Spike, ½" NPT, Black CX-646-BK 8" ABS Spike, ½" NPT, Black CX-646-BK 8" ABS Spike, ½" NPT, Stainless Steel CX-646-SS 8" ABS Spike, ½" NPT, Stainless Steel CX-647-BK 10.5" Heavy Duty ABS Spike, ½" NPT, Black

Mounting Risers

CX-682B-GM	6" Brass Riser, ½ NPT Male/Female, Gun Metal
CX-683B-GM	12" Brass Riser, ½ NPT Male/Female, Gun Metal
CX-684B-GM	18" Brass Riser, ½ NPT Male/Female, Gun Metal
CX-685B-GM	24" Brass Riser, ½ NPT Male/Female, Gun Metal

27/8"

Mounting Canopies

CX-705B-GM	Brass Flat Canopy, ½ NPT, Gun Metal
CX-709B-GM	Brass Raised Canopy, ½ NPT, Gun Metal
CX-718B-GM	5" Brass Canopy, 3-Hole ½ NPT, Gun Metal





Cable Connectors

CX-854	Direct Burial Silicone Filled Wire Nut, Tan
CX-858	Speedy Cable Connector, Supply Cable up to 10-2, Black
CX-839	Universal cable connector, Supply cable up to 8-2, one/Pack Black

(2)

1633 Staunton Ave Los Angeles, CA 90021 TEL. FAX. (800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

E-Mail: sales@coronalighting.com

Cast Brass

CX-682B-GM 6'

CX-683B-GM 12"

CX-684B-GM 18"

CX-685B-GM 24"

³/4"

CX-705B-GM

15/8"

CX-854