

(213) 747-3234

(213) 747-4500

FAX. (800) 727-9957 (800) 727-9262



SPECIFICATION SHEET

E-Mail: sales@coronalighting.com

PRODUCT #: CL-735B-GM

Path Lights

Knuckle:

Wiring:

Cast Brass

Fixture Specifications:

Housing & Shroud: Corrosion Resistant Cast Brass.

Stem: 24" solid brass pipe with ½ in NPT on bottom.

18" stem also available.

Finish: GM- Gun Metal. Natural toning process.

GM finish will vary due to artistic process.

Also available in AB, and SI.

Clear and heat resistant convex glass. Lens:

> Top grade fixed ceramic bi-pin socket, with retension clip to securely hold lamp in place.

Lamp: 12V, MR-16, 50W max.

Socket:

Available in LED (3.5W & 5W) or without lamp. See the Lamp Guide below for more information.

Gasket: Silicone double gasketed for water tight sealing

Adjustable cast brass knuckle with thumb screw.

Fixture is prewired with a 3ft 18-2 SPT2-W direct

burial cord. Wire connector sold seperately. Universal connector (CX-839) and silicone filled wire nut (CX-854) are available from Corona

Lighting.

Mounting Spike: Standard injection molded spike with 1/2" NPT

threaded female hub.

Electrical Notes: A remote 12V transformer is required. Options are

available from Corona Lighting.

Voltage range for LED lamps are 9V-17V.


Some assembly needed. Proper grease/lubricant is suggested on threaded parts during installation.

Limited lifetime warranty on fixture housing and Warranty:

stem against manufacturer's defects.







AVAILABLE LED LAIVIF3 (Corona LED lamps have a five (5) year limited warranty against manufacturer's defect	LAMPS (Corona LED lamps have a five (5) year limited warranty against manufacturer's defects)
---	---

		BEAM		COLOR &	RATED	HALOGEN		
LAMP NUMBER	WATTS	SPREAD	LUMEN	TEMP.	HOURS	EQUIVALENT		
L-ED16-3W-SP	3.5	15° Spot	270	2700K	50,000	25 Watt		
L-ED16-3W-FL	3.5	45° Flood	270	2700K	50,000	25 Watt		
L-ED16-3W-WF	3.5	60° Wide Flood	270	2700K	50,000	25 Watt		
L-ED16-5W-SP	5	15° Spot	350	2700K	50,000	40 Watt		
L-ED16-5W-FL	5	45° Flood	350	2700K	50,000	40 Watt		
L-ED16-5W-WF	5	60° Wide Flood	350	2700K	50,000	40 Watt		
L-ED16-COB5W-SP	5	15° Spot	450	2700K	50,000	50 Watt		
L-ED16-COB5W-FL	5	38° Flood	450	2700K	50,000	50 Watt		
L-ED16-COB5W-WF	5	60° Wide Flood	450	2700K	50,000	50 Watt		
L-ED16-COB5W-SP3K	5	15° Spot	470	3000K	50,000	50 Watt		
L-ED16-COB5W-FL3K	5	38° Flood	470	3000K	50,000	50 Watt		
L-ED16-COB5W-WF3K	5	60° Wide Flood	470	3000K	50,000	50 Watt		
■ Single color MR-16 LED available in AMBER, BLUE, GREEN, PURPLE, RED and VIOLET								

FL

JOB INFORMATION

TYPE: DATE:

JOB NAME & ADDRESS:

PRODUCT #:

TOTAL QUANTITY:

LAMP TYPE & WATTAGE:

TRANSFORMER:

CONTRACTOR:

SPECIFIER:

When ordering LED lamp with a fixture your part number should follow the format below:

• CL - product # - Length - lamp - wattage - lamp angle 12 CL - 735B-GM -- L-ED16 -5W -

Example: CL-735B-GM-12-L-ED16-5W-FL

Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.



WWW.CORONALIGHTING.COM

ARCHITECTURAL GRADE SERIES

ACCESSORIES SHEET

1633 Staunton Ave Los Angeles, CA 90021

TEL. FAX. (800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

E-Mail: sales@coronalighting.com

•Path Lights

Cast Brass

Mounting Pedestals

CX-601-BK 1" PVC Mounting Pedestal, ½" NPT, **Black**

PRODUCT #: CL-735B-GM


CX-601-VG 1" PVC Mounting Pedestal, ½" NPT, Verde Green

CX-603-BK 3" PVC Mounting Pedestal, ½" NPT Female Brass Hub

on top, Black

CX-603-VG 3" PVC Mounting Pedestal, ½" NPT Female Brass Hub

on top, Verde Green



CX-604-BK 1" PVC Adjustable Mounting Pedestal, ½" NPT, Black

CX-621-BK 1" PVC Cap, ½" NPT, **Black**

CX-621-VG 1" PVC Cap, ½" NPT, Verde Green

CX-622-BK 2" PVC Cap, ½" NPT, **Black**

CX-622-VG 2" PVC Cap, ½" NPT, Verde Green

CX-624-BK 3" PVC Cap, ½" NPT Female Brass Hub, **Black**

CX-624-VG $\,\,$ 3" PVC Cap, $\frac{1}{2}$ " NPT Female Brass Hub, Verde Green

Ground Spikes

CX-642-BK 8.5" ABS Spike, ½" NPT, **Black**CX-642-BZ 8.5" ABS Spike, ½" NPT, **Bronze**

CX-643-BZ 8.5" ABS Spike, ½" NPT, **Bronze**



CX-646-BK 8" ABS Spike, ½" NPT, Black

CX-646-BR 8" ABS Spike, ½" NPT, **Natural Brass**CX-646-SS 8" ABS Spike, ½" NPT, **Stainless Steel**

CX-647-BK 10.5" Heavy Duty ABS Spike, ½" NPT, Black

Mounting Risers

CX-682B-GM 6" Brass Riser, ½ NPT Male/Female, **Gun Metal**CX-683B-GM 12" Brass Riser, ½ NPT Male/Female, **Gun Metal**CX-684B-GM 18" Brass Riser, ½ NPT Male/Female, **Gun Metal**CX-685B-GM 24" Brass Riser, ½ NPT Male/Female, **Gun Metal**

Mounting Canopies

CX-705B-GM Brass Flat Canopy, ½ NPT, **Gun Metal**CX-709B-GM Brass Raised Canopy, ½ NPT, **Gun Metal**CX-718B-GM 5" Brass Canopy, 3-Hole ½ NPT, **Gun Metal**







ARCHITECTURAL GRADE SERIES

ACCESSORIES SHEET

1633 Staunton Ave Los Angeles, CA 90021

TEL. FAX. (800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

E-Mail: sales@coronalighting.com

PRODUCT #: CL-735B-GM

Special Lenses & Honeycomb Louvers

CX-238 MR-16 Snap-on holder, Silver Plated
CX-239 MR-16 honeycomb louver, Black
CX-240-AM MR-16 color lens, Amber

CX-240-BL MR-16 color lens, Blue
CX-240-GR MR-16 color lens, Green
CX-240-RD MR-16 color lens, Red
CX-240-YL MR-16 color lens, Yellow
CX-241 MR-16 lens, Linear Spread
CX-242 MR-16 lens, Frosted

CX-242 MR-16 lens, **Frosted**CX-243 MR-16 lens, **Prismatic**

• For MR-16 Lenses and Louvers, you will need the CX-238



• Path Lights

• Cast Brass

Cable Connectors

CX-854 Direct Burial Silicone Filled Wire Nut, Tan
 CX-858 Speedy Cable Connector, Supply Cable up to 10-2, Black
 CX-839 Universal cable connector, Supply cable up to 8-2,

one/Pack Black



