

SPECIFICATION SHEET

 1633 Staunton Ave

 Los Angeles, CA
 90021

 TEL.
 FAX.

 (800) 727-9262
 (800) 727-9957

 (213) 747-4500
 (213) 747-3234

E-Mail: sales@coronalighting.com

BK- Black. (GR finish is discontinued) Electrical Notes: A remote 12V transformer is required. Options are available from Corona Lighting. Lens: None Voltage range for 12V halogen lamps are 11V-12.5° Socket: Top-grade ceramic bi-pin socket, with retension clip. Voltage range for LED lamps are 10V-17V. Lamp: 12V, MR-16 halogen 50W max. L-BAB-C20 (20w) standard. LED lamps are also available. See lamp guide, below for more information. Warranty: One (1) year warranty on fixture and housing again manufacturer's defects			# : C	CL-381			• Hang	ging Light	• Aluminum
Finish: Br. Black (<i>GF finish is discontinued</i>) Br. Black (<i>GF finish is discontinued</i>)Anarging cable. Anarging cable.Lanns: None Socket: Top-grade ceramic bi-pin socket, with retension clip. 12V, MR-16 halogen SW max. L-BAB-C20 (20W) guida, below for more information.Electrical Notes: Top-grade ceramic bi-pin socket, with retension clip. 12V, MR-16 halogen SW max. L-BAB-C20 (20W) guida, below for more information.Warranty: Warranty:None Cone (1) year warranty on fisture and housing again mandacture's defectsWiring: Fourier or wardable separately. One Universal conceptor (VX-839) to two salitoned filled wither nuts (2x CX-854) may be ordered to Corona Lighting.Warranty:One (1) year warranty on fisture and housing again mandacture's defectsWiring: Fourier or wardable separately. One Universal conceptor (VX-839) to two allicons filled withe nuts (2x CX-854) may be ordered to Corona Lighting.So the top of top of the top of t	Fixture	Specif	icatio	ons:					
Finish: Polyester UV powder coaled available in BK-Bisck. (<i>RF finish is discontinued</i>) Lans: None Socket: Top-grade certamic bi-jin socket, with refension clip. 12V, MF-16 halogen software. LBAS C20 (20) stude, below for more information. Electrical Notes: Wiring: Fittice is prewired with a 5-fit 16-2 BPTI-W cord. Wire connector available separately. One Universal connector (X-439) or two silicone filled wire nuts (2x CX-884) may be ordered to Corona Lighting. Soket: Erectrical Notes: BK-Green finish shown S.S.W and SW Warranty: Oblige region 12/2 halogen approximation. Warranty: Oblige region 12/2 halogen approximation. Warranty: Consection 12/2 halogen approximation. Warranty: Warranty: Warranty: Software Softw	Housing:	Die-cast alu	uminum				Mount	ing:	
Lens: None Voltage range for 210 halogen lamps are 111-120. Socket: Top-grade ceramic bi-pin socket, with retension cip. Voltage range for LED lamps are also available. See lamp guide, below for more information. Voltage range for LED lamps are 100-172. Wirking: Fixture is prewider with a 5-fi 18-2 SPT1-W cord. Warranty: Warranty: One (1) year warranty on fixture and housing again manufacture's defects. Wirking: Fixture is prewider with a 5-fi 18-2 SPT1-W cord. Wirking: Fixture is prewider with a 5-fi 18-2 SPT1-W cord. Wirking: Fixture is prewider with a 5-fi 18-2 SPT1-W cord. Wirking: Fixture is prewider with a 5-fi 18-2 SPT1-W cord. Wirking: Fixture is prewider with a 5-fi 18-2 SPT1-W cord. Fixture is prewider with a 5-fi 18-2 SPT1-W cord. Warranty: BR-Green finish shown Socket Socket Socket Socket Socket Socket Socket Socket Socket Socket ValladeLE LED LAMPS (corona Lighting Socket Socket Socket Socket LED 16-SW-FP Si Socket Socket Socket Socket Socket Socket Socket Socket Socket Socket Socket Socket Socket Socket Socket Socket Socket Socket Socket Socket Socket Socke	Finish:						Electri	ical Notes:	A remote 12V transformer is required. Options are
Socket: Lam: Top-grade caramic bi-pin socket, with retension clip. Voltage range for LDB lamps are 100.V17V. Proper grade.LDB lamps are 100.V17V. Proper grade.LDB lamps are 100.V17V. Weraded parts during installation process. Wiring: Future is prevised with 5 ft 18:2 SPT1-W cord. Wire connector vaniable separately. One Universal connector (CX-38) to how silcores filled wire nuts (2x CX-884) may be ordered to Corona Lighting. Warranty: Warranty: One (1) year warranty on fixture and housing again manufacture's defects Order of walls Defected to Corona Lighting. Image for the second sec	Lens:	None							0 0
Lamp: 12,V. MR-16 halogen 50W max. LBAB-C20 (20W) standard. LED lamps are also available. See lamp guide. See la	Socket:	Top-grade o	ceramic	bi-pin socket w	ith retensi	on clip			
$ \begin{array}{c} \mbox{transford} \ LED lamps are also available. See lamp guide, below for more information. \\ \end{tabular} \ Warranty: \\ tabula$				•					
Wiring: Fixture is previned with a 5-4 18-2 SPT 1-W cord. Wire connector (X-439) or two silicone filled wire nuis (2x CX-854) may be ordered to Corona Lighting. Sector (X-439) ordered to Corona Lighting. Generation of the sector (X-439) ordered to Corona Lighting. Sector (X-439) ordered to Corona Lighting. Generation of the sector (X-439) ordered to Corona Lighting. Sector (X-439) ordered to Corona Lighting. Sector (X-439) ordered to Corona Lighting. Generation of the sector of the se	·	standard. I	LED lam	ips are also avai	,	,	Warra	nty:	One (1) year warranty on fixture and housing again
$ \begin{array}{c} \hline \\ \hline $	Wiring:	Wire conne connector (ctor ava	ilable seperately) or two silicone	/. One Un filled wire	iversal nuts			
LAMP NUMBER WATTS SPREAD LUMEN TEMP. HOURS EQUIVALENT TYPE: DATE: L-ED16-3W-SP 3.5 15° Spot 270 2700K 50,000 25 Watt JOB NAME & ADDRESS: JOB NAME & ADDRESS: JOB NAME & ADDRESS: L-ED16-3W-FL 3.5 60° Wide Flood 270 2700K 50,000 25 Watt JOB NAME & ADDRESS: JOB NAME & ADDRESS: L-ED16-SW-SP 5 15° Spot 350 2700K 50,000 40 Watt JOB NAME & ADDRESS: JOB NAME & A			5	B					5 5/"
L-ED16-3W-SP 3.5 15° Spot 270 2700K 50,000 25 Watt JOB NAME & ADDRESS: L-ED16-3W-FL 3.5 60° Wide Flood 270 2700K 50,000 25 Watt JOB NAME & ADDRESS: L-ED16-3W-WF 3.5 60° Wide Flood 270 2700K 50,000 25 Watt JOB NAME & ADDRESS: L-ED16-5W-SP 5 15° Spot 350 2700K 50,000 40 Watt PRODUCT #: L-ED16-COB5W-FL 5 45° Flood 350 2700K 50,000 50 Watt TOTAL QUANTITY: L-ED16-COB5W-SP 5 15° Spot 450 2700K 50,000 50 Watt TAME & WATTAGE: L-ED16-COB5W-FL 5 38° Flood 450 2700K 50,000 50 Watt TRANSFORMER: L-ED16-COB5W-FL 5 38° Flood 450 2700K 50,000 50 Watt TRANSFORMER: L-ED16-COB5W-FL3K 5 38° Flood 470 3000K 50,000 50 Watt TRANSFORMER: L-ED16-COB5W-WF3K 5 60° Wide Flood 470 3000K 50,000	AVAILABL				e a five (5) ve				31/2 [™] →
L-ED16-3W-FL 3.5 45° Flood 270 2700K 50,000 25 Watt JOB NAME & ADDRESS: L-ED16-3W-WF 3.5 60° Wide Flood 270 2700K 50,000 25 Watt PRODUCT #: L-ED16-5W-SP 5 15° Spot 350 2700K 50,000 40 Watt TOTAL QUANTITY: L-ED16-SW-WF 5 60° Wide Flood 350 2700K 50,000 40 Watt TOTAL QUANTITY: L-ED16-COB5W-SP 5 15° Spot 450 2700K 50,000 50 Watt LAMP TYPE & WATTAGE: L-ED16-COB5W-FL 5 38° Flood 450 2700K 50,000 50 Watt TRANSFORMER: L-ED16-COB5W-FL 5 38° Flood 450 2700K 50,000 50 Watt TRANSFORMER: L-ED16-COB5W-SP3K 5 15° Spot 470 3000K 50,000 50 Watt TRANSFORMER: L-ED16-COB5W-WF3K 5 15° Spot 470 3000K 50,000 50 Watt SPECIFIER: L-ED16-COB5W-WF3K 5 60° Wide Flood 470 3000K 50,000 50 Watt </th <th>AVAILABL</th> <th></th> <th></th> <th>prona LED lamps have</th> <th></th> <th>ar limited warrar</th> <th>ty against man</th> <th>ufacturer's defects</th> <th>31/2[™]→</th>	AVAILABL			prona LED lamps have		ar limited warrar	ty against man	ufacturer's defects	31/2 [™] →
L-ED16-3W-WF 3.5 45 Flood 270 2700K 50,000 25 Watt L-ED16-3W-WF 3.5 60° Wide Flood 270 2700K 50,000 25 Watt L-ED16-5W-SP 5 15° Spot 350 2700K 50,000 40 Watt PRODUCT #: L-ED16-5W-FL 5 45° Flood 350 2700K 50,000 40 Watt TOTAL QUANTITY: L-ED16-COB5W-SP 5 15° Spot 450 2700K 50,000 50 Watt TAMP TYPE & WATTAGE: L-ED16-COB5W-FL 5 38° Flood 450 2700K 50,000 50 Watt TRANSFORMER: L-ED16-COB5W-WF 5 60° Wide Flood 450 2700K 50,000 50 Watt TRANSFORMER: L-ED16-COB5W-SP3K 5 15° Spot 470 3000K 50,000 50 Watt TRANSFORMER: L-ED16-COB5W-FL3K 5 38° Flood 470 3000K 50,000 50 Watt SPECIFIER:		E LED LAI	MPS (Co	orona LED lamps have	N	ear limited warrar	ty against man	ufacturer's defects	$3^{1}/_{2}^{1}$
L-ED16-5W-SP 5 15° Spot 350 2700K 50,000 40 Watt PRODUCT #: L-ED16-5W-FL 5 45° Flood 350 2700K 50,000 40 Watt TOTAL QUANTITY: L-ED16-COB5W-SP 5 15° Spot 450 2700K 50,000 50 Watt LAMP TYPE & WATTAGE: L-ED16-COB5W-FL 5 38° Flood 450 2700K 50,000 50 Watt TOTAL QUANTITY: L-ED16-COB5W-FL 5 38° Flood 450 2700K 50,000 50 Watt TRANSFORMER: L-ED16-COB5W-WF 5 60° Wide Flood 450 2700K 50,000 50 Watt TRANSFORMER: L-ED16-COB5W-SP3K 5 15° Spot 470 3000K 50,000 50 Watt TRANSFORMER: L-ED16-COB5W-WF3K 5 60° Wide Flood 470 3000K 50,000 50 Watt SPECIFIER:	LAMP NU	E LED LAI	MPS (Co <u>watts</u> 3.5	orona LED lamps have BEAN SPREAD 15° Spot	LUMEN 270	ear limited warrar COLOR & TEMP. 2700K	nty against man RATED HOURS 50,000	ufacturer's defects HALOGEN EQUIVALENT 25 Watt	$3\frac{1}{2}$
L-ED16-5W-FL 5 45° Flood 350 2700K 50,000 40 Watt TOTAL QUANTITY: L-ED16-COB5W-SP 5 15° Spot 450 2700K 50,000 50 Watt LAMP TYPE & WATTAGE: L-ED16-COB5W-FL 5 38° Flood 450 2700K 50,000 50 Watt TOTAL QUANTITY: L-ED16-COB5W-FL 5 38° Flood 450 2700K 50,000 50 Watt TRANSFORMER: L-ED16-COB5W-WF 5 60° Wide Flood 450 2700K 50,000 50 Watt TRANSFORMER: L-ED16-COB5W-SP3K 5 15° Spot 470 3000K 50,000 50 Watt CONTRACTOR: L-ED16-COB5W-FL3K 5 38° Flood 470 3000K 50,000 50 Watt SPECIFIER:	LAMP NU L-ED16-3W- L-ED16-3W-	E LED LAI MBER SP FL	MPS (Co watts 3.5 3.5	orona LED lamps have BEAN SPREAD 15° Spot 45° Flood	LUMEN 270 270	ear limited warrar _ COLOR & _ TEMP. 2700K 2700K	nty against man RATED HOURS 50,000 50,000	ufacturer's defects HALOGEN EQUIVALENT 25 Watt 25 Watt	$3\frac{1}{2}$
L-ED16-5W-WF 5 60° Wide Flood 350 2700K 50,000 40 Watt TOTAL QUANTITY: L-ED16-COB5W-SP 5 15° Spot 450 2700K 50,000 50 Watt LAMP TYPE & WATTAGE: L-ED16-COB5W-FL 5 38° Flood 450 2700K 50,000 50 Watt TRANSFORMER: L-ED16-COB5W-WF 5 60° Wide Flood 450 2700K 50,000 50 Watt TRANSFORMER: L-ED16-COB5W-SP3K 5 15° Spot 470 3000K 50,000 50 Watt CONTRACTOR: L-ED16-COB5W-WF3K 5 60° Wide Flood 470 3000K 50,000 50 Watt SPECIFIER:	LAMP NU L-ED16-3W-1 L-ED16-3W-1 L-ED16-3W-1	E LED LAI MBER SP FL WF	MPS (Co watts 3.5 3.5 3.5	Drona LED lamps have BEAN SPREAD 15° Spot 45° Flood 60° Wide Flood	LUMEN 270 270 270 270	ear limited warrar COLOR & TEMP. 2700K 2700K 2700K	nty against man RATED HOURS 50,000 50,000 50,000	ufacturer's defects HALOGEN EQUIVALENT 25 Watt 25 Watt 25 Watt	JOB INFORMATION TYPE: DATE: JOB NAME & ADDRESS:
L-ED16-COB5W-FL 5 38° Flood 450 2700K 50,000 50 Watt L-ED16-COB5W-WF 5 60° Wide Flood 450 2700K 50,000 50 Watt TRANSFORMER: L-ED16-COB5W-SP3K 5 15° Spot 470 3000K 50,000 50 Watt TRANSFORMER: L-ED16-COB5W-FL3K 5 38° Flood 470 3000K 50,000 50 Watt SECIFIER: L-ED16-COB5W-WF3K 5 60° Wide Flood 470 3000K 50,000 50 Watt SECIFIER:	LAMP NU ED16-3W- ED16-3W- ED16-3W- ¹ ED16-5W- ²	E LED LAI MBER SP FL WF SP	MPS (Co watts 3.5 3.5 3.5 5	Drona LED lamps have BEAN SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot	M LUMEN 270 270 270 350	ear limited warrar COLOR & TEMP. 2700K 2700K 2700K 2700K	ty against man RATED HOURS 50,000 50,000 50,000 50,000	ufacturer's defects HALOGEN EQUIVALENT 25 Watt 25 Watt 25 Watt 40 Watt	JOB INFORMATION TYPE: DATE: JOB NAME & ADDRESS:
L-ED16-COB5W-WF 5 60° Wide Flood 450 2700K 50,000 50 Watt TRANSFORMER: L-ED16-COB5W-SP3K 5 15° Spot 470 3000K 50,000 50 Watt CONTRACTOR: L-ED16-COB5W-FL3K 5 38° Flood 470 3000K 50,000 50 Watt SPECIFIER: L-ED16-COB5W-WF3K 5 60° Wide Flood 470 3000K 50,000 50 Watt SPECIFIER:	LAMP NU L-ED16-3W- L-ED16-3W- L-ED16-3W- L-ED16-5W- L-ED16-5W-	E LED LAI MBER SP FL WF SP FL	MPS (Co watts 3.5 3.5 3.5 5 5 5	Drona LED lamps have BEAN SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood	LUMEN 270 270 270 270 350 350	ear limited warrar COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K	ty against man RATED HOURS 50,000 50,000 50,000 50,000 50,000	ufacturer's defects HALOGEN EQUIVALENT 25 Watt 25 Watt 25 Watt 40 Watt 40 Watt	JOB INFORMATION TYPE: DATE: JOB NAME & ADDRESS: PRODUCT #:
L-ED16-COB5W-SP3K 5 15° Spot 470 3000K 50,000 50 Watt L-ED16-COB5W-FL3K 5 38° Flood 470 3000K 50,000 50 Watt L-ED16-COB5W-WF3K 5 60° Wide Flood 470 3000K 50,000 50 Watt SPECIFIER:	LAMP NU L-ED16-3W- L-ED16-3W- L-ED16-3W- L-ED16-5W- L-ED16-5W- L-ED16-5W- L-ED16-COE	E LED LAI MBER SP FL WF SP FL WF 35W-SP	MPS (Co watts 3.5 3.5 3.5 5 5 5 5 5	BEAN BEAN SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood 60° Wide Flood	LUMEN 270 270 270 350 350 350	ear limited warran COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K 2700K	ty against man RATED HOURS 50,000 50,000 50,000 50,000 50,000 50,000	HALOGEN EQUIVALENT 25 Watt 25 Watt 25 Watt 40 Watt 40 Watt 40 Watt	JOB INFORMATION TYPE: JOB NAME & ADDRESS: PRODUCT #: TOTAL QUANTITY:
L-ED16-COB5W-FL3K 5 38° Flood 470 3000K 50,000 50 Watt L-ED16-COB5W-WF3K 5 60° Wide Flood 470 3000K 50,000 50 Watt SPECIFIER:	LAMP NU L-ED16-3W- L-ED16-3W- L-ED16-5W- L-ED16-5W- L-ED16-5W- L-ED16-COE L-ED16-COE	E LED LAI MBER SP FL WF SP FL WF 35W-SP 35W-SP	MPS (Co watts 3.5 3.5 3.5 5 5 5 5 5 5 5 5 5	BEAN BEAN SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood 60° Wide Flood 15° Spot 38° Flood	LUMEN 270 270 270 350 350 350 450 450	ear limited warran COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K	ty against man RATED HOURS 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000	ufacturer's defects HALOGEN EQUIVALENT 25 Watt 25 Watt 25 Watt 40 Watt 40 Watt 40 Watt 50 Watt 50 Watt	JOB INFORMATION TYPE: JOB NAME & ADDRESS: PRODUCT #: TOTAL QUANTITY: LAMP TYPE & WATTAGE:
L-ED16-COB5W-WF3K 5 60° Wide Flood 470 3000K 50,000 50 Watt SPECIFIER:	LAMP NU L-ED16-3W-1 L-ED16-3W-1 L-ED16-5W-1 L-ED16-5W-1 L-ED16-5W-1 L-ED16-COE L-ED16-COE L-ED16-COE	E LED LAI MBER SP FL WF SP FL WF 35W-SP 35W-SP 35W-FL 35W-WF	MPS (Co watts 3.5 3.5 3.5 5 5 5 5 5 5 5 5 5	BEAN BEAN SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood 60° Wide Flood 15° Spot 38° Flood 60° Wide Flood	LUMEN 270 270 270 350 350 350 450 450	ear limited warran COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K	ty against man RATED HOURS 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000	ufacturer's defects HALOGEN EQUIVALENT 25 Watt 25 Watt 25 Watt 40 Watt 40 Watt 40 Watt 50 Watt 50 Watt 50 Watt	JOB INFORMATION TYPE: JOB NAME & ADDRESS: PRODUCT #: TOTAL QUANTITY: LAMP TYPE & WATTAGE:
	LAMP NU L-ED16-3W-1 L-ED16-3W-1 L-ED16-5W-1 L-ED16-5W-1 L-ED16-5W-1 L-ED16-COE L-ED16-COE L-ED16-COE	E LED LAI MBER SP FL WF SP FL WF 35W-SP 35W-SP 35W-VF 35W-SP3K	MPS (Co watts 3.5 3.5 3.5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	BEAN BEAN SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood 60° Wide Flood 15° Spot 38° Flood 60° Wide Flood 15° Spot	LUMEN 270 270 270 350 350 350 450 450 450 470	ear limited warran COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 3000K	ty against man RATED HOURS 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000	ufacturer's defects HALOGEN EQUIVALENT 25 Watt 25 Watt 25 Watt 40 Watt 40 Watt 40 Watt 50 Watt 50 Watt 50 Watt 50 Watt	JOB INFORMATION TYPE: JOB NAME & ADDRESS: PRODUCT #: TOTAL QUANTITY: LAMP TYPE & WATTAGE: TRANSFORMER:
	LAMP NU L-ED16-3W-1 L-ED16-3W-1 L-ED16-5W-1 L-ED16-5W-1 L-ED16-COE L-ED16-COE L-ED16-COE L-ED16-COE L-ED16-COE	E LED LAI MBER SP FL WF SP FL 35W-SP 35W-SP 35W-FL 35W-WF 35W-SP3K 35W-SP3K	MPS (Co watts 3.5 3.5 3.5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	BEAN BEAN SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood 60° Wide Flood 15° Spot 38° Flood 60° Wide Flood 15° Spot 38° Flood	LUMEN 270 270 270 350 350 450 450 470 470	Aar limited warran COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 3000K 3000K 3000K	ty against man RATED HOURS 50,000	ufacturer's defects HALOGEN EQUIVALENT 25 Watt 25 Watt 25 Watt 40 Watt 40 Watt 40 Watt 50 Watt 50 Watt 50 Watt 50 Watt 50 Watt 50 Watt	JOB INFORMATION TYPE: JOB NAME & ADDRESS: PRODUCT #: TOTAL QUANTITY: LAMP TYPE & WATTAGE: TRANSFORMER: CONTRACTOR:

CL - 381 - BK - L-ED16 - 5W - FL

• Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.

Example: CL-381-BK-L-ED16-5W-FL