

SDECIFICATION SHEET

1633 Staunton Ave Los Angeles, CA 90021 FAX. TEL. (800) 727-9262(800) 727-9957(213) 747-4500(213) 747-3234

aaliabi

PROD	UCT #	: C	L-707			•Path	Lights	• Aluminun
Fixture	Specific	catio	ons:					
Housing:	Die-cast alur	minum				Wiring	:	Fixture is prewired with a 3ft, 18-2 direct burial cord
Stem:	Die-cast alur	mining	tubing stem.					Wire connector sold seperately. Universal connector (CX-839) and silicone filled wire nut (CX-854) are
Finish:	Polyester U\ and GR- Gre	•	ler coated, avai	able in B l	K- Black,			available from Corona Lighting.
Lens:			nd heat resistar	nt glass.		Mounti	ng Spike:	6" black aluminum spike with ½" NPT threaded female hub.
Socket:			eramic bi-pin soo	•		Electric	al Notes:	A remote 12V transformer is required. Options are
Lamp:		LED (3	nax. 3.5W & 5W) or v de below for mo					available from Corona Lighting. Voltage range for LED lamps are 9V-17V. Proper grease/lubricant is suggested on threaded parts during installation process.
Gasket:			isket, tightly sea tight protection	-	to housing	Warran	ty:	One (1) year warranty on fixture and stem against manufacturer's defects.
	Finish Shown		ona I ED lamos have	a five (5) ve		E D V and 5	W	3"" 23 ³ /4" 23 ³ /4" 6" <u>6</u> "
		PS (Corr	ona LED lamps have BEAN			V and 5	W	s) JOB INFORMATION
	E LED LAMF MBER W	ATTS	BEAM	LUMEN	ear limited warrai _ COLOR & _ TEMP.	V and 5 hty against man RATED HOURS	W ufacturer's defect HALOGEN EQUIVALEN	s) JOB INFORMATION TYPE: DATE:
AVAILABLE	E LED LAMF MBER W	ATTS 3.5	BEAM SPREAD 15° Spot	LUMEN 270	ear limited warran COLOR & TEMP. 2700K	V and 5 hty against man RATED HOURS 50,000	W ufacturer's defect HALOGEN EQUIVALEN 25 Watt	s) JOB INFORMATION TYPE: DATE:
LAMP NUM -ED16-3W-5 -ED16-3W-F	E LED LAMF MBER W SP ::	ATTS 3.5 3.5	BEAM	LUMEN	ear limited warrai _ COLOR & _ TEMP.	V and 5 hty against man RATED HOURS	W ufacturer's defect HALOGEN EQUIVALEN	S) JOB INFORMATION TYPE: DATE: JOB NAME & ADDRESS:
LAMP NUM -ED16-3W-5 -ED16-3W-F -ED16-3W-V	E LED LAMF MBER W/ SP :: 'L : VF :	ATTS 3.5 3.5 3.5	BEAM SPREAD 15° Spot 45° Flood 60° Wide Flood	LUMEN 270 270 270 270	ear limited warran _ COLOR & TEMP. 2700K 2700K	V and 5 hty against man RATED HOURS 50,000 50,000 50,000	W ufacturer's defect HALOGEN EQUIVALEN 25 Watt 25 Watt 25 Watt	s) JOB INFORMATION TYPE: DATE:
LAMP NUM -ED16-3W-5 -ED16-3W-F -ED16-3W-V -ED16-5W-5 -ED16-5W-F	E LED LAMF MBER W/ SP :: 'L : VF : SP :L	ATTS 3.5 3.5	BEAM SPREAD 15° Spot 45° Flood	LUMEN 270 270	ear limited warran _ COLOR & _ TEMP. 2700K 2700K 2700K	V and 5 hty against man RATED HOURS 50,000 50,000	W ufacturer's defect HALOGEN EQUIVALEN 25 Watt 25 Watt	S) JOB INFORMATION TYPE: DATE: JOB NAME & ADDRESS:
LAMP NUM -ED16-3W-5 -ED16-3W-F -ED16-3W-V -ED16-5W-5 -ED16-5W-F	E LED LAMF MBER W/ SP :: 'L : VF : SP :L	ATTS 3.5 3.5 3.5 5 5	BEAM SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot	LUMEN 270 270 270 350	ear limited warran _ COLOR & TEMP. 2700K 2700K 2700K	N and 5 aty against man RATED HOURS 50,000 50,000 50,000 50,000 50,000 50,000	W ufacturer's defect HALOGEN EQUIVALEN 25 Watt 25 Watt 25 Watt 40 Watt	S) JOB INFORMATION TYPE: DATE: JOB NAME & ADDRESS: PRODUCT #:
LAMP NUM -ED16-3W-5 -ED16-3W-F -ED16-3W-V -ED16-5W-5 -ED16-5W-F -ED16-5W-V -ED16-COB	E LED LAMF	ATTS 3.5 3.5 3.5 5 5 5 5 5	BEAN SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood 60° Wide Flood 15° Spot	LUMEN 270 270 270 350 350 350 450	ear limited warran COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K	V and 5 nty against man RATED HOURS 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000	W ufacturer's defect HALOGEN EQUIVALENT 25 Watt 25 Watt 25 Watt 40 Watt 40 Watt 40 Watt 40 Watt 50 Watt	s) JOB INFORMATION TYPE: DATE: JOB NAME & ADDRESS: PRODUCT #: TOTAL QUANTITY: LAMP TYPE & WATTAGE:
LAMP NUM -ED16-3W-5 -ED16-3W-F -ED16-3W-V -ED16-5W-5 -ED16-5W-F -ED16-5W-V -ED16-COB -ED16-COB	IED LAMF MBER W SP 5 CL 5 VF 5 SP 5 SP 5 SP 5 SP 5	ATTS 3.5 3.5 3.5 5 5 5 5 5 5 5 5	BEAN SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood 60° Wide Flood 15° Spot 38° Flood	LUMEN 270 270 270 350 350 350 450 450	ear limited warran - COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K	V and 5 nty against man RATED HOURS 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000	W ufacturer's defect HALOGEN EQUIVALENT 25 Watt 25 Watt 25 Watt 40 Watt 40 Watt 40 Watt 40 Watt 50 Watt 50 Watt	s) JOB INFORMATION TYPE: DATE: JOB NAME & ADDRESS: PRODUCT #: TOTAL QUANTITY:
LAMP NUM -ED16-3W-5 -ED16-3W-F -ED16-3W-V -ED16-5W-5 -ED16-5W-F -ED16-5W-V -ED16-COB -ED16-COB -ED16-COB -ED16-COB	IED LAMF MBER W SP S L S VF S SP S SW-SP S SW-WF S	ATTS 3.5 3.5 3.5 5 5 5 5 5 5 5 5 5 5 5	BEAM SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood 60° Wide Flood 15° Spot 38° Flood 60° Wide Flood	LUMEN 270 270 270 350 350 350 350 450 450 450	ear limited warran COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K	Nand 5 nty against man RATED HOURS 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000	W ufacturer's defect HALOGEN EQUIVALEN 25 Watt 25 Watt 25 Watt 40 Watt 40 Watt 40 Watt 50 Watt 50 Watt 50 Watt	s) JOB INFORMATION TYPE: DATE: JOB NAME & ADDRESS: PRODUCT #: TOTAL QUANTITY: LAMP TYPE & WATTAGE:
LAMP NUM -ED16-3W-5 -ED16-3W-F -ED16-3W-V -ED16-5W-5 -ED16-5W-4 -ED16-5W-4 -ED16-COB -ED16-COB -ED16-COB -ED16-COB	IED LAMF MBER W SP SP SL SP SP SP SW-SP SW-SP 5W-SP3K SW-SP3K	ATTS 3.5 3.5 3.5 5 5 5 5 5 5 5 5 5 5 5 5 5	BEAN SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood 60° Wide Flood 15° Spot 38° Flood 60° Wide Flood	LUMEN 270 270 270 350 350 350 350 450 450 450 450 450	ear limited warran COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 3000K	N and 5 nty against man RATED HOURS 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000	W ufacturer's defect HALOGEN EQUIVALEN 25 Watt 25 Watt 25 Watt 40 Watt 40 Watt 40 Watt 40 Watt 50 Watt 50 Watt 50 Watt	s) JOB INFORMATION TYPE: DATE: JOB NAME & ADDRESS: PRODUCT #: TOTAL QUANTITY: LAMP TYPE & WATTAGE: TRANSFORMER: CONTRACTOR:
LAMP NUM -ED16-3W-5 -ED16-3W-F -ED16-3W-V -ED16-5W-5 -ED16-5W-F -ED16-5W-V -ED16-COB -ED16-COB -ED16-COB -ED16-COB	IED LAMF MBER W SP SP SL SP SP SP SW-SP SW-SP SW-SP SW-WF SW-SP3K SW-FL3K	ATTS 3.5 3.5 3.5 5 5 5 5 5 5 5 5 5 5 5	BEAM SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood 60° Wide Flood 15° Spot 38° Flood 60° Wide Flood	LUMEN 270 270 270 350 350 350 350 450 450 450	ear limited warran COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K	Nand 5 nty against man RATED HOURS 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000	W ufacturer's defect HALOGEN EQUIVALEN 25 Watt 25 Watt 25 Watt 40 Watt 40 Watt 40 Watt 50 Watt 50 Watt 50 Watt	S) JOB INFORMATION TYPE: DATE: JOB NAME & ADDRESS: PRODUCT #: TOTAL QUANTITY: LAMP TYPE & WATTAGE: TRANSFORMER:

• CL - product # - color - lamp - wattage - lamp angle Example: CL-707-BK-L-ED16-5W-FL CL - 707 - BK - L-ED16 - 5W - FL

1



ACCESSORIES SHEET

 1633 Staunton Ave

 Los Angeles, CA
 90021

 TEL.
 FAX.

 (800) 727-9262
 (800) 727-9957

 (213) 747-4500
 (213) 747-3234

E-Mail: sales@coronalighting.com

LUE GRADE			E-Mail: sales@coronalighting.co
PROD	UCT # : CL-707	 Path Lights 	• Aluminum
Nounting	Pedestals	Ground Sp	bikes
CX-601-BK	1" PVC Mounting Pedestal, ½" NPT, Black	CX-642-BK	8.5" ABS Spike, ½" NPT, Black
CX-601-VG	1" PVC Mounting Pedestal, ½" NPT, Verde Green	CX-642-BZ	8.5" ABS Spike, ½" NPT, Bronze
CX-603-BK	3" PVC Mounting Pedestal, ½" NPT Female Brass Hub on top, Black	CX-643-BZ	8.5" ABS Spike, ½" NPT, Bronze
X-603-VG	3" PVC Mounting Pedestal, ½" NPT Female Brass Hub on top, Verde Green	-	10½"
	← 18"		СХ-647-ВК
		CX-646-BK	8" ABS Spike, ½" NPT, Black
	СХ-603-ВК	CX-646-BR	8" ABS Spike, ½" NPT, Natural Brass
		CX-646-SS	8" ABS Spike, ½" NPT, Stainless Steel
CX-604-BK	1" PVC Adjustable Mounting Pedestal, ½" NPT, Black	CX-647-BK	10.5" Heavy Duty ABS Spike, ½" NPT, Black
CX-621-BK	1" PVC Cap, ½" NPT, Black		
X-621-VG	1" PVC Cap, 1/2" NPT, Verde Green		
CX-622-BK	2" PVC Cap, ½" NPT, Black		
X-622-VG	2" PVC Cap, 1/2" NPT, Verde Green		
CX-624-BK	3" PVC Cap, ½" NPT Female Brass Hub, Black	Mounting F	Pisors
CX-624-VG	3" PVC Cap, 1/2" NPT Female Brass Hub, Verde Green	CX-671	6" Aluminum Riser, ½ NPT Male/Female
		CX-071	Finishes: BK - Black, BZ - Bronze, GR - Green, GT - Granite, RT - Rust, VG - Verde Green, WH - White
-	Canopies	CX-672	12" Aluminum Riser, ½ NPT Male/Female Finishes: BK- Black, BZ- Bronze, GR- Green, GT- Granite, RT- Rust, VG- Verde Green, WH- White
CX-703	Aluminum tree mount canopy ½ NPT Finishes: BK - Black, BZ - Bronze, GR - Green, GT - Granite, RT - Rust, VG - Verde Green, WH - White	CX-673	18" Aluminum Riser, ½ NPT Male/Female Finishes: BK- Black, BZ- Bronze, GR- Green, GT- Granite, RT- Rust, VG- Verde Green, WH- White
			СХ-671-ВК 6″
			СХ-672-ВК 12″
	СХ-703-ВК		
			CX-673-BK 18"



ACCESSORIES SHEET

1633 Staunton Ave Los Angeles, CA 90021 TEL. FAX. (800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

E-Mail: sales@coronalighting.com

PRODUCT # : CL-707

Special Lenses & Honeycomb Louvers

CX-238	MR-16 Snap-on holder, Silver Plated
CX-239	MR-16 honeycomb louver, Black
CX-240-AM	MR-16 color lens, Amber
CX-240-BL	MR-16 color lens, Blue
CX-240-GR	MR-16 color lens, Green
CX-240-RD	MR-16 color lens, Red
CX-240-YL	MR-16 color lens, Yellow
CX-241	MR-16 lens, Linear Spread
CX-242	MR-16 lens, Frosted
CX-243	MR-16 lens, Prismatic

• For MR-16 Lenses and Louvers, you will need the CX-238



Cable Connectors

CX-854	Direct Burial Silicone Filled Wire Nut, Tan
CX-858	Speedy Cable Connector, Supply Cable up to 10-2, Black
CX-839	Universal cable connector, Supply cable up to 8-2, one/Pack Black









