

SPECIFICATION SHEET

Los Angeles, CA 90021 FAX. TEL. (800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

1633 Staunton Ave

F-Mail: sales@coronalighting.com

1

	UCT # : C				•Path L	ights	Solid Brass	
Fixture	Specificatio	ons:						
Housing:	Corrosion resistant	- Corrosion resistant Solid Brass "L" shaped design			Wiring:		Fixture is prewired with a 3ft, 18-2 direct burial cord Wire connector sold seperately. Universal connector (CX-839) and silicone filled wire nut (CX-854) are	
Stem:	Solid brass pipe wi	Solid brass pipe with ½" NPT on bottom						
Finish:	GM- Gun Metal. Natural toning process.						available from Corona Lighting.	
		lso in AB , and SI finishes. Aluminum options vailable in BK and BZ			Mounting Spike:		Standard injection molded spike with $\frac{1}{2}$ " NPT thread female hub.	
Lens:		High impact, sandblasted, heat resistant clear glass. Extra frosted and linear lenses included.			Electric	al Notes:	A remote 12V transformer is required. Options are available from Corona Lighting.	
Socket:	Top grade fixed ceramic bi-pin socket. Easy tool-free lamp access.					Voltage range for LED lamps are 8V-21V. Proper grease/lubricant is suggested on threaded parts during installation process.		
Lamp: Designed to use a 12V, T3 LED lamp only. Available in LED (2W & 2.5W) or without lamp. See the Lamp Guide below for more information. Not to be used with halogen/xenon lamps.				Warrant	y:	Limited lifetime warranty on fixture housing against manufacturer's defects.		
						Ţ		
AVAILABLI	E LED LAMPS (Core	ona LED lamos hi	ave a fi ve (5) vez	L E 2W &	_	81/2"		
	E LED LAMPS (Cord	BE	AM	ar limited warra	nty against manu RATED	Ifacturer's defect	u	
EDT3-2W	R WATTS	BE SPREAD 360°	AM LUMEN 200	ar limited warra COLOR & TEMP. 2700K	nty against manu RATED HOURS 25,000	ifacturer's defect HALOGEN EQUIVALEN 20 Watt	NT TYPE: DATE:	
. AMP NUMBE EDT3-2W EDT3-2.5W	R WATTS	BE/ SPREAD 360° 180°	AM LUMEN 200 240	ar limited warra COLOR & TEMP. 2700K 2700K	Anty against manu RATED HOURS 25,000 25,000	ifacturer's defect HALOGEN EQUIVALEN 20 Watt 35 Watt	· · · · · · · · · · · · · · · · · · ·	
EDT3-2W EDT3-2.5W EDT3-2.5W EDT3-2W-3 EDT3-2.5W	WATTS 2 2.5 3K 2 /-3K 2.5	SPREAD 360° 180° 360° 180°	AM LUMEN 200 240 210 250	ar limited warra COLOR & TEMP. 2700K 2700K 3000K 3000K	RATED HOURS 25,000 25,000 25,000 25,000	ifacturer's defect HALOGEN EQUIVALEN 20 Watt 35 Watt 20 Watt 35 Watt	TYPE: DATE:	
EDT3-2W EDT3-2.5W EDT3-2.5W	R WATTS 2 2 / 2.5 3K 2 /-3K 2.5 2 2	BE/ SPREAD 360° 180° 360°	AM LUMEN 200 240 210	ar limited warra COLOR & TEMP. 2700K 2700K 3000K	anty against manu RATED HOURS 25,000 25,000 25,000	ifacturer's defect HALOGEN EQUIVALEN 20 Watt 35 Watt 20 Watt	NT TYPE: DATE:	

CL - 717B-GM - L-EDT3 - 2W-3K

• Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.



Mounting Canopies

CX-705B-GM	Brass Flat Canopy, ½ NPT, Gun Metal
CX-709B-GM	Brass Raised Canopy, ½ NPT, Gun Metal
CX-718B-GM	5" Brass Canopy, 3-Hole ½ NPT, Gun Metal





Cable Connectors

CX-854	Direct Burial Silicone Filled Wire Nut, Tan
CX-858	Speedy Cable Connector, Supply Cable up to 10-2, Black
CX-839	Universal cable connector, Supply cable up to 8-2, one/Pack Black

CX-684B-GM 18"

CX-683B-GM 12"

