



WWW.CORONALIGHTING.COM

ARCHITECTURAL GRADE SERIES

SPECIFICATION SHEET

1633 Staunton Ave

Los Angeles, CA 90021

TEL.

FAX.

(800) 727-9262

(800) 727-9957

(213) 747-4500

(213) 747-3234

E-Mail: sales@coronalighting.com

PRODUCT # : CL-648C-RC

•Area Lights

•Solid Copper

Fixture Specifications:

Housing: Corrosion resistant solid copper.

Stem: Solid copper pipe with 1/2" NPT on bottom.

Finish: RC- Raw Copper. Will age gradually over time.

Lens: Frosted polycarbonate, cover over lamp providing sprinkler water protection.

Socket: Top grade fixed ceramic bi-pin socket. Easy tool free lamp access.

Lamp: 12V T3 LED.
Available in 3W Bluetooth Mesh RGB-WW;
2W, 2.5W LED or without lamp.
See the Lamp Guide below for more information.

Wiring:

Fixture is prewired with a 3-ft 18-2 SPT2-W direct burial cord. Wire connector sold separately.

Quick-locking connectors are available from Corona Lighting (CX-LOC) find details on page 2.

Mounting Spike:



Standard injection molded spike with 1/2" NPT threaded female hub.

Electrical Notes:

A remote 12V transformer is required. Options are available from Corona Lighting (see page 3). Voltage range for BT lamps are 9-17V, LED are 8-21V. Proper grease/lubricant is suggested on threaded parts during installation process.

Warranty:

Limited lifetime warranty on fixture housing and stem against manufacturer's defects.



AVAILABLE LED LAMPS

(Corona LED lamps have a five (5) year limited warranty against manufacturer's defects)

LAMP NUMBER	WATTS	BEAM SPREAD	LUMEN	COLOR & TEMP.	RATED HOURS	HALOGEN EQUIVALENT
L-EDT3-3W-BT*	0.5-3	360°	10-200	2200K-5700K	50,000	---
L-EDT3-2W	2	360°	200	2700K	25,000	20 Watt
L-EDT3-2.5W	2.5	180°	240	2700K	25,000	35 Watt
L-EDT3-2W-3K	2	360°	210	3000K	25,000	20 Watt
L-EDT3-2.5W-3K	2.5	180°	250	3000K	25,000	35 Watt
L-EDT3-AM*	2	360°	170	2000K	25,000	20 Watt

* AM- Amber color

For more additional Lamps, and accessories visit Coronalighting.com

JOB INFORMATION

TYPE: DATE:

JOB NAME & ADDRESS:

PRODUCT #:

TOTAL QUANTITY:

LAMP TYPE & WATTAGE:

TRANSFORMER:

CONTRACTOR:

SPECIFIER:

• When ordering a halogen or xenon lamp add lamp number to the product number. If you are ordering LED lamps you should follow the format below:

• CL - **product #** - **lamp** - **wattage**

Example: CL-648C-RC-L-EDT3-2W-3K

CL - 648C-RC - L-EDT3 - 2W-3K


• Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixture without further notification.

ACCESSORIES SHEET

PRODUCT # :CL-648C-RC

Mounting Pedestals

CX-601-BK	1" PVC Mounting Pedestal, 1/2" NPT, Black
CX-601-VG	1" PVC Mounting Pedestal, 1/2" NPT, Verde Green
CX-603-BK	3" PVC Mounting Pedestal, 1/2" NPT Female Brass Hub on top, Black
CX-603-VG	3" PVC Mounting Pedestal, 1/2" NPT Female Brass Hub on top, Verde Green


CX-603-BK

CX-604-BK	1" PVC Adjustable Mounting Pedestal, 1/2" NPT, Black
CX-621-BK	1" PVC Cap, 1/2" NPT, Black
CX-621-VG	1" PVC Cap, 1/2" NPT, Verde Green
CX-622-BK	2" PVC Cap, 1/2" NPT, Black
CX-622-VG	2" PVC Cap, 1/2" NPT, Verde Green
CX-624-BK	3" PVC Cap, 1/2" NPT Female Brass Hub, Black
CX-624-VG	3" PVC Cap, 1/2" NPT Female Brass Hub, Verde Green

Mounting Canopies

CX-705B-BR	Brass Flat Canopy, 1/2 NPT, Natural Brass
CX-709B-BR	Brass Raised Canopy, 1/2 NPT, Natural Brass


CX-709B-BR


CX-705B-BR

- Area Lights

- Solid Copper

Ground Spikes

CX-642-BK	8.5" ABS Spike, 1/2" NPT, Black
CX-642-BZ	8.5" ABS Spike, 1/2" NPT, Bronze
CX-643-BZ	8.5" ABS Spike, 1/2" NPT, Bronze


CX-647-BK

CX-646-BK	8" ABS Spike, 1/2" NPT, Black
CX-646-BR	8" ABS Spike, 1/2" NPT, Natural Brass
CX-646-SS	8" ABS Spike, 1/2" NPT, Stainless Steel
CX-647-BK	10.5" Heavy Duty ABS Spike, 1/2" NPT, Black

Mounting Risers

CX-682C-RC	6" Copper Riser, 1/2 NPT Male/Female, Raw Copper
CX-683C-RC	12" Copper Riser, 1/2 NPT Male/Female, Raw Copper
CX-684C-RC	18" Copper Riser, 1/2 NPT Male/Female, Raw Copper
CX-685C-RC	24" Copper Riser, 1/2 NPT Male/Female, Raw Copper


CX-682C-RC 6"


CX-683C-RC 12"

CX-684C-RC 18"

CX-685C-RC 24"

Cable Connectors

CX-LOC	Quick-locking Cable Connectors, Tan (Installation Instructions)
--------	---





WWW.CORONALIGHTING.COM

ARCHITECTURAL GRADE SERIES

1633 Staunton Ave
Los Angeles, CA 90021

TEL. FAX.

(800) 727-9262 (800) 727-9957
(213) 747-4500 (213) 747-3234

E-Mail: sales@coronalighting.com

ACCESSORIES SHEET

PRODUCT # :CL-648C-RC

• Area Lights

• Solid Copper

Stainless Steel Pool and Spa Rated Transformers

T-LTF60 60W, 12V, Compact Mini Transformer

T-LT75 75W, 12 and 15V, Single Circuit Transformer w/ Integrated Mechanical Timer.

T-LT150 150W, 12-15V, Single Circuit Transformer.

T-LT300 300W, 12-15V, Single Circuit Transformer.

T-LT600 600W, 12-15V, Dual Circuit Transformer.

T-LT900 900W, 12-22V, Triple Circuit Transformer.

T-FIDT Field Installed Plug-in Digital Timer.

T-FIT Field Installed Plug-in Mechanical Timer.

T-TR-FIP Field Installed Plug-in Photocell



T-LT75



T-LT150



T-FIDT



T-LT300



T-TR-FIP

Dimmers

CX-DIM-100 100W, Low Voltage Dimmer Switch.
Use with T-LT Series Transformers, **Black**



CX-DIM-100