

SPECIFICATION SHEET

PRODUCT # : CL-110B-GM

• Down Lights

• Cast Brass

Fixture Specifications:

Housing: Corrosion resistant cast brass.

Finish: **GM- Gun Metal.** Natural toning process. GM finish will vary due to artistic process. Also available in **AB- Antique Bronze** finish.

Lens: Clear and heat resistant tempered flat glass

Socket: Top grade fixed ceramic bi-pin socket, with lamp retention clip to securely hold lamp in place.

Lamp: Two 12V, MR-16, 50W max. Available in 2xLED (3.5W or 5W) or without lamps. See the Lamp Guide below for more information.


Wiring: Fixture is prewired with a 25-ft 18-2 SPT2-W direct burial cord. Wire connector sold separately. Silicone filled direct burial wire nut (**CX-854**) and quick-locking connectors (**CX-LOC**) are available from Corona Lighting.

Gasket: Silicone gaskets for water-tight sealing

Mounting: Stainless Steel mounting screws with anchor bolts

Applications: Outdoor Living Spaces, Porches, Garages, Pool Cages and Pergolas

Electrical Notes: A remote 12V transformer is required. Options are available from Corona Lighting. Voltage range for LED lamps are 9V-17V. Proper grease/lubricant is suggested on threaded parts during installation process.

Warranty: Limited lifetime warranty on fixture housing against manufacturer's defects.


AVAILABLE LED LAMPS (Corona LED lamps have a five (5) year limited warranty against manufacturer's defects)

LAMP NUMBER	WATTS	BEAM		COLOR & TEMP.	RATED HOURS	HALOGEN EQUIVALENT
		SPREAD	LUMEN			
L-ED16-3W-SP	3.5	15° Spot	270	2700K	50,000	25 Watt
L-ED16-3W-FL	3.5	45° Flood	270	2700K	50,000	25 Watt
L-ED16-3W-WF	3.5	60° Wide Flood	270	2700K	50,000	25 Watt
L-ED16-5W-SP	5	15° Spot	350	2700K	50,000	40 Watt
L-ED16-5W-FL	5	45° Flood	350	2700K	50,000	40 Watt
L-ED16-5W-WF	5	60° Wide Flood	350	2700K	50,000	40 Watt
L-ED16-COB5W-SP	5	15° Spot	450/470	2700K/3000K	50,000	50 Watt
L-ED16-COB5W-FL	5	38° Flood	450/470	2700K/3000K	50,000	50 Watt
L-ED16-COB5W-WF	5	60° Wide Flood	450/470	2700K/3000K	50,000	50 Watt
L-ED16-6W-SP	6	15° Spot	600	2700K/3000K	50,000	75 Watt
L-ED16-6W-FL	6	38° Flood	600	2700K/3000K	50,000	75 Watt
L-ED16-6W-WF	6	60° Wide Flood	600	2700K/3000K	50,000	75 Watt

■ Single color MR-16 LED available in AMBER, BLUE, GREEN, PURPLE, RED and VIOLET

JOB INFORMATION

TYPE: DATE:

JOB NAME & ADDRESS:

PRODUCT #:

TOTAL QUANTITY:

LAMP TYPE & WATTAGE:

TRANSFORMER:

CONTRACTOR:

SPECIFIER:

• When ordering LED lamp with a fixture your part number should follow the format below:

• CL - product # - lamp - wattage - lamp angle

CL - 102B-GM - L-ED16 - 3W - SP

Example: CL-102B-GM-L-ED16-3W-SP

• Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixture without further notification.

ACCESSORIES SHEET


PRODUCT # : CL-110B-GM

Down Lights

• Cast Brass

Cable Connectors

- CX-854 Direct Burial Silicone Filled Wire Nut, **Tan**
CX-LOC Quick-locking gel filled wire connector
Two / Pack, **Tan**



CX-LOC



CX-854

Special Lenses & Honeycomb Louvers

- CX-238 MR-16 Snap-on holder, **Silver Plated**
CX-239 MR-16 honeycomb louver, **Black**
CX-240-AM MR-16 color lens, **Amber**
CX-240-BL MR-16 color lens, **Blue**
CX-240-GR MR-16 color lens, **Green**
CX-240-RD MR-16 color lens, **Red**
CX-240-YL MR-16 color lens, **Yellow**
CX-241 MR-16 lens, **Linear Spread**
CX-242 MR-16 lens, **Frosted**
CX-243 MR-16 lens, **Prismatic**

For MR-16 Lenses and Louvers, you will need the CX-238

