

SPECIFICATION SHEET

PRODUCT # : CL-445-BT-BK

• Fence/Wall Lights

• Cast Brass

Housing: Corrosion Resistant Cast Brass

Finish: **BK-** Black Brass
Also available in **AB** and **WH**

Light Source: 1W- 3W RGB-WW LED module. Lumen output is between 20LM - 150LM. Allows for 90° beam spread. 20W Halogen Equivalent, 50,000 Rated Hours, 2700K-5000K color temperature, CRI: >90

LED Features: 2.4 ghz External antenna and Reset button.
CCT Options: Presets: 2700K, 3000K, 4000K, 5000K
RGB : Unlimited color wheel options & quick presets.
Dimming: Every color choice
Scenes: Customizable scenes with up to 8 colors.
Compatibility: Amazon's Alexa* and Google Home*
(*CX-BTG gateway required, see below)
Music: The lights will follow music collected by a device's microphone.

Connection: Bluetooth Mesh, *Range Extender (CX-BTE) is highly recommended, see below for details.*

Antenna: External, 2.4 GHZ

Ambient Temp: -13° Fahrenheit to 140° Fahrenheit



Wiring: Fixture is prewired with a 10-ft 18-2 SPT-1W direct burial cord, Wire connector sold separately. Quick-locking connectors (**CX-LOC**) are available from Corona Lighting, see page 2 for details

Mounting: Surface mounted, best used for Walls, Fence Posts, Around Pools, and Other Outdoor Living Areas

Electrical Notes: A remote 12V transformer is required. Options are available from Corona Lighting, see page 2 for info. Voltage range for LED module is 9-17V AC/DC (2.57VA). Proper grease/lubricant is suggested on threaded parts during installation process.


IP Rating IP67

Warranty: Lifetime Warranty on Fixture Housing. Ten Year Warranty on LED Module



SMART ACCESSORIES

CX-BTE Bluetooth Range Extender
CX-BTG Wireless Bluetooth Mesh Gateway



JOB INFORMATION

TYPE: DATE:

JOB NAME & ADDRESS:

PRODUCT #:

TOTAL QUANTITY:

LAMP TYPE & WATTAGE:

TRANSFORMER:

CONTRACTOR:

SPECIFIER:

ACCESSORIES SHEET

PRODUCT # : CL-445-BT-BK

• Fence/Wall Lights

• Cast Brass

Stainless Steel Pool and Spa Rated Transformers

T-LTF60	60W, 12V, Compact Mini Transformer
T-LT75	75W, 12 and 15V, Single Circuit Transformer w/ Integrated Mechanical Timer.
T-LT150	150W, 12V-15V, Single Circuit Transformer.
T-LT300	300W, 12-15V, Single Circuit Transformer.
T-LT600	600W, 12-15V, Dual Circuit Transformer.
T-LT900	900W, 12-22V, Triple Circuit Transformer.
T-FIDT	Field Installed Plug-in Digital Timer.
T-FIT	Field Installed Plug-in Mechanical Timer.
T-TR-FIP	Field Installed Plug-in Photocell



T-LT75



T-LT150



T-FIDT



T-LT300




T-TR-FIP

Cable Connectors

CX-LOC	Quick-locking Cable Connectors, Tan (Installation Instructions)
--------	--

CX-LOC



T-LT600

